

TECHNICAL DATA	
RR 125 4T ENDURO	
CHASSIS	and de III
Frame	steel double cradle frame
Wheel base	1403 mm
Max length	2145 mm
Max width	800 mm
Max height	1200 mm
Seat height	915 mm
Ground clearance	295 mm
Footrest height	363 mm
Dry weight	101,0 kg
Fuel tank capacity	6,0 l.
Reserve	1 l.
Front suspension	Hydraulic fork with ø40 mm shaft
Rear suspension	Monoshock with adjustable spring preload
Shock absorber stroke	50 mm
Front wheel travel	245 mm
Rear wheel travel	220 mm
Front brake	disc ø260 mm
Rear brake	disc ø220 mm
Front rim	21 x 1,6 - 36 holes
Rear rim	18 x 1,85 - 36 holes
Front tyre	80/90-21 standard homol. 90/90-21
	110/80-18 standard homol.120/90-18 or 120/80-
Rear tyre	18
ENGINE	
Type	Single-cylinder, 4-stroke, air cooled
Bore	54,0 mm
Stroke	54,0 mm
Displacement	124cc
Compression ratio	10:1
Ignition	Electronic Moriyama F5HH
Spark plug	NGK R CR7 HSA/ NHSP LD AGRTC
Lubrication	Forced with pump
Feeding	Unleaded gasoline
Carburettor	PTK \phi20
Clutch	Wet multi-disc clutch
Primary trasmission	Z. 20/68
Transmission	5 speed
Secondary trasmission	Z. 14/54
Secondary trasmission Engine oil	SAE 15W/50
Eligille oil	SAL 1344/30